

Comparatif des détendeurs Tecline

	R 1 PRO / R 1 PRO O ₂	R 2 ICE	R 2 ICE Special	R 5 ICE	R 5 ICE Special	R 2 TEC / R 2 TEC O ₂	R 5 TEC	V 2	R 3 OCTO	R 3 TEC OCTO
										
1er étage	R 1 PRO / R 1 PRO O₂	R 2 ICE	R 2 ICE Special	R 5 ICE	R 2 ICE Special	R 2 ICE / R 2 ICE O₂	R 5 TEC Black	V 2 ICE		
Protection contre le givrage		■	■	■	■	■	■	■		
Tourelle rotative		■				■				
Nbre de ports MP/HP	4 / 1	4 / 2	4 / 2	4 / 2	4 / 2	4 / 2	4 / 2	2 / 1		
Type	piston	membrane	membrane	membrane	membrane	membrane	membrane	membrane		
Pression maximale	300 bar	300 bar	300 bar	300 bar	300 bar	300 bar	300 bar	300 bar		
Valeur de la moyenne pression	9,5 bar	9,0 bar	9,0 bar	9,0 bar	9,0 bar	9,0 bar	9,0 bar	9,0 bar		
Débit maximal à 20 MPa	3823 l/min	3823 l/min	3823 l/min	3823 l/min	3823 l/min	3823 l/min	3823 l/min	3823 l/min		
Ports en angles							■	■		

InnoDive